


THE NEXT GENERATION OF REFRIGERATION EQUIPMENT FOR A2L'S IS HERE!



Outdoor Condensing Unit



Safety shut-off valves are shipped loose with the evaporator and field installed outside of the walk-in cooler/freezer.



Evaporator



ADDED COMPONENTS
For Leak Detection and
Mitigation System



Leak sensors
are pre-
installed and
mounted in the
evaporator.



Mitigation
strategy
incorporated
into our
SMARTVAP+
controller.

WE ARE PREPARED!

Our factory-installed leak detection and mitigation strategy incorporates the safety mechanisms required for A2L refrigerants. This low GWP new generation of equipment will be easy for today's technicians to service.

Our A2L equipment is designed for R454A, R454C & R455A refrigerants.

Bally systems meet the January 1, 2026 requirement that all new commercial refrigeration products use a refrigerant <300 GWP (R-454A) for systems under 200 Lbs. and <150 GWP (R-454C & R-455A) for systems above 200 Lbs.

Our equipment will be ready to order once final certifications are completed.



Brantford, Ontario – Longview, Texas
b-rp.com

We design and manufacture a complete line of commercial refrigeration products.
Find out more at b-rp.com or call us at (519) 751-0444 or 1-800-463-9517

1112168
01/12/24